


ECOPLUS

The economical solution for hot-melt adhesive dispensing. Dramatically increase production quality and efficiency where traditional bonding methods are used.





Features

1

1 litre tank with one connection for applicator head.
3 litre tank with two connections (one on each side) for applicator heads.

4

Non-stick coated tank with open top access allows easy, clean filling.
Tank is directly pressurized for glue dispensing; up to 3 bar pressure.

2

Air-Open / Spring-Close Ball & Seat module design.
Application tailored mounting of applicator head.
Multiple module adaptability; up to 5 modules per applicator head.

5



Glue dispensing activation/control using foot operated switch, sensor or PLC program.
Integrated pattern control – dispense glue as dots or lines with precise control.

3

Up to 750 cartons per hour per operator.

6


In-built batch and master counter.
Buzzer notification after every set number of counts available as option.
Time switch with scheduled auto start/stop available as option.







Technical Specifications

Machine Make	Mahisa
Features	PLC with built in HMI Foot-switch or sensor operated Shut-off valve for pressure release
Electrical Service	230-240 VAC, 1 phase, 50 Hz
Output Capability	1 no. (for EcoPlus 11); Max. 2 nos. (for EcoPlus 32)
Heating Time	Approx. 30 minutes
Tank Capacity (Volume)	1L (for EcoPlus 11); 3L (for EcoPlus 32)
Tank Pressure	0.2 – 3 bar
Operating System Pressure	4 – 5 bar
Control temperature Range	20 – 185 °C







Dimensions: EcoPlus 11





Dimensions: EcoPlus 32







Contact Us

Mahisa Packaging Systems LLP

9/314, Jogani Industrial Complex,
Mumbai, MH – 400022, India.

- Website: www.mahisa.com
- Email: info@mahisa.com
- Phone: [+91 98210 49426](tel:+919821049426)



MAHISA



Click on the icons for respective links